AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

 (Withdrawn): A system for automatically configuring I/O devices, comprising: means for determining physical locations of the I/O devices with respect to one another; and

means for assigning node addresses to each I/O device, each assigned node address corresponding to the physical location of the respective I/O devices.

(Withdrawn): A system for automatically configuring I/O devices, comprising: a plurality of I/O devices operatively coupled to each other;

a sub-system for determining physical locations of the I/O devices with respect to one another, the sub-system assigning node addresses to each I/O device – each assigned node address corresponding to the physical location of the respective I/O devices.

 (Withdrawn): A method for automatically configuring I/O devices, comprising the steps of:

determining physical locations of the I/O devices with respect to one another; and assigning node addresses to each I/O device, each assigned node address corresponding to the physical location of the respective I/O devices.

4. (Currently amended): An adaptable control system for providing network communications, comprising:

a physical media for providing communications to at least one I/O module, wherein the physical media includes a first protocol and a second protocol, the first protocol to enable the at least one I/O module to receive the network communications and the second protocol to provide the network communications to the at least one enabled I/O module; and

the at least one I/O module enables at least one other I/O module to form an I/O group *via* the first protocol.

- 5. (Cancelled).
- (Currently amended): The system of claim 4, wherein the second protocol provides at least one of DeviceNet. EtherNet and ControlNet network communications.
- (Currently amended): The system of claim 4, further comprising an interface for providing a pass-thru for the network communications.
- (Currently amended): The system of claim 7, wherein the interface provides a DC/DC converter for supplying I/O power and enabling the at least one other I/O module.
- (Currently amended): The system of claim 4, further comprising an adapter for establishing network communications.
- 10. (Currently amended): The system of claim 9, wherein the adapter includes at least one processor for enabling the at least one I/O module.
- 11. (Currently amended): The system of claim 9, wherein the adapter includes an Offlink Connection Manager (OCM) object, a node list, and an I/O data table.

- 12. (Currently amended): The system of claim 42 wherein the at least one I/O module includes a processor for receiving the first protocol as an input and providing the first protocol as an output.
- 13. (Withdrawn): A method for providing an adaptable control system, comprising the steps of:

receiving network communications via an interface; sequentially enabling at least one I/O module to receive the network communications from the interface; and enabling at least one other I/O module to form an I/O group.

- (Withdrawn): The method of claim 13 further comprising the step of: using a PointBus input to enable a PointBus output to initiate a network connection
- 15. (Withdrawn): The method of claim 14 further comprising the steps of: waiting for the PointBus input; determining a network address for the at least one I/O module; and enabling the at least one other I/O module to receive a network address after determining the network address for the at least one I/O module.
- 16. (Withdrawn): An adaptable control system, comprising: means for receiving network communications; means for sequentially enabling at least one I/O module to receive the network communications; and

means for enabling at least one other I/O module to receive a network address after determining the network address for the at least one I/O module.

17. (Withdrawn): The system of claim 16 further comprising: means for using a PointBus input to enable a PointBus output to initiate a network connection.

- 18. (New): The system of claim 4, the at least one other I/O module being added sequentially to the I/O group utilizing output from the at least one I/O module.
- 19. (New): The system of claim 4, the at least one I/O module and the at least one other I/O module being automatically configured.
- 20. (New): The system of claim 4, further comprising a sub-system that determines respective physical locations of the at least one I/O module and the at least one other I/O module.
- 21. (New): The system of claim 20, the sub-system assigns node addresses to the at least one I/O module and the at least one other I/O module, the node addresses correspond to the respective physical locations.